

Serial No. 10/765,257

Atty Dkt No. 706599US2

IN THE CLAIMS

The following listed claims will replace all prior versions and listing of claims in this application.

RECEIVED
CENTRAL FAX CENTER

AUG 23 2006

Listing of Claims

1 – 9 (Cancelled)

10. (Currently amended) A bolt lock for preventing rotation of a bolt relative to a workpiece comprising:

a locking plate having a ring-shaped body, a first extension extending from said ring-shaped body, and a second extension extending from said ring-shaped body;

wherein said ring-shaped body includes a first plurality of bendable locking tabs, said first extension includes a second plurality of bendable locking tabs, and said second extension includes a third plurality of bendable locking tabs,

wherein said first plurality of bendable locking tabs are movable between an engaged position contacting a head of said bolt and a disengaged position retracted from said head of said bolt.

wherein said second plurality of bendable locking tabs are movable between an engaged position contacting a second head of a second bolt, used for securing the locking plate to the workpiece, to prevent rotation of the second bolt, and a disengaged position removed from said second head of said second bolt, and

wherein said third plurality of bendable locking tabs are movable between an engaged position contacting a third head of a third bolt, used for securing the locking plate to the workpiece, to prevent rotation of the third bolt, and a disengaged position removed from said third head of said third bolt.

Serial No. 10/765,257

Atty Dkt No. 706599US2

11. (Previously presented) The bolt lock of claim 10, wherein said ring-shaped body, said first extension, and said second extension are formed of a single piece of material.

12. (Currently amended) The bolt lock of claim ~~10~~ 11, wherein said first plurality of tabs ~~are includes four tabs equally~~ spaced apart along a ~~radial~~ radially inner edge of said ring-shaped body.

13. (Currently amended) The bolt lock of claim ~~10~~ 12, wherein said second plurality of bendable locking tabs project radially outwardly from said first extension and wherein said third plurality of bendable locking tabs project radially outwardly from said second extension.

14. – 22. (Cancelled)